



APPLICATION

The HD Plastic Floor Plate 46T protects hard and stabilized substrates from damage by heavy loads, such as truck and forklifts. The plate can also be used as support for any type of temporary construction (scaffolding, sets, stages ...).

CHARACTERISTICS

- Material : Recycled flexible PVC
- Weight : 35 kg
- Load capacity : Up to 46T/m² (1), depending on the quality of the floor
- **Dimensions** : 120 cm x 80,5 cm x 3 cm
- Ramps (optional available)

(1) Result per m² for a load evenly distributed over the entire surface and not concentrated locally, subject to report D-280720-06298 - 21 AOUT 2020.

Note 1 : Depending on the use, the supported load and the quality and porosity of the floor, the use of the HD Plastic Floor Plate 46T may not prevent markings on the surfaces to be protected. Therefore, to reduce the risk, we recommend the use of a protective underlayment (tested and approved by you).

Note 2 : Intended for installation on hard and/or stabilized floors.

Note 3 : An installation of the Floor Plate without a ramp reduces the life of the plates (at the level of the groove of locking). As well as posing an increased risk to staff and the public as it increases the chance of falling/stumbling. The use of ramps (optionally available) at the edges is therefore strongly recommended.

Note 4 : This product is not suitable for road traffic.

Tolerance of +/- 10% to the stated sizes.